

Dlp Audio b.v. Qube audio
Kleiweg 12
5145 NB Waalwijk
www.qubeaudio.nl



QS 115 Subwoofer

Subwoofer speaker system, 1x15"

The QS 115 subwoofer is the ideal companion for QUBE models Q 110 and Q112 two way speaker systems providing extended low frequency reinforcement down to 38Hz. A 15" front facing dual coil woofer is housed in a compact bass reflex designed cabinet and can handle 1200 watts continuous and deliver 132 dB SPL. The QS 115 when used with the Q110 or Q112 creates a powerful 3 way system for FOH, stage side fills as well as for drum and keyboard monitoring applications. Equipped with a 1 $\frac{3}{8}$ " (35mm) top mount speaker stand socket and six M -10 fly points, the QS115 cabinet is constructed with 18 mm. (3/4") Baltic birch plywood that is also internally braced to prevent undesired resonance and is finished with a durable scratch and scuff resistant black paint.

Configuration	Bass Reflex
Recommended Amplifier	Watts (RMS) 1200
Long term power	Watts 600
Short term power (IEC 268-5)	Watts 2400
Nominal impedance	ohms 4
Frequency response @ -6dB	38Hz – 400Hz
Low frequency woofer	15" – 4" voice coil
Sensitivity (@ 1W/1m)	dB 98,5
Maximum SPL	dB 132
Recommended External Crossover frequency	Hz 100
Dispersion	Omnidirectional
Recommended HP filter	30Hz-24dboct
Recommended external controller	SP 22D Qube plug in module
Input connectors	2 speakon NL-4
Net dimensions (WxHxD)	cm 48x89x60 (18.9" x 35" x 23.6")
Net weight	Kg 47 (lbs 103,5)

